1000 SERIES CASTORS

The 1000 Series 1000kg load rating provides an economical alternative to heavier load bearing castors. The ability to be towed at a 6kph by tugs and tractors enables this castor to be used on mobile platforms, aviation trolleys, automotive assembly lines and production manufacturing plants.

The polyurethane cast iron wheel type with a rolling diameter of up to 300mm not only enhances maneuverability but decreases rolling resistance. Like most Richmond heavy duty castors, our 1000 series has a precision machined ball race and high tensile steel kingpin to withstand side impact loads.

MOUNTING PLATES AVAILABLE IF REQUIRED page 95

UP TO TODOKG/CASTOR


S6338SLB

SPECIFICATIONS & FITTINGS

$\mathbf{\hat{O}}$	Ū	0	0	0	KG	G		U.	I	
Diameter (mm)	Width (mm)	Wheel Type	Wheel Code	Bearing Type	Load Capacity	Height (mm)	Swivel Radius	Rigid Code	Swivel Code	
150	50	Poly Ci	PU659	Ball	900/700	194	130	R6339	S6338	9
150	45	Cast Iron	Ci601	Ball	1000/500	194	130	R6319	S6318	
200	50	Poly Ci	PU876	Ball	1000/750	248	155	R8069	S8068	9
200	50	Cast Iron	Ci852	Ball	1000/500	248	155	R8089	S8088	
250	50	Poly Ci	PU1056	Ball	1000/750	300	180	R1020	S1019	9
300	50	Poly Ci	PU1218	Ball	1000/750	360	215	R1205	S1204	

To order castor with Brake and/ or 4 Way Directional Lock, add B and/or D to the end of Swivel Code e.g. S6138B indicates a brake castor.
g denotes towable castors. Also available with Swivel Lock and Brake add SLB to the end of the Swivel Code e.g. S6138SLB.

BASEPLATE DIMENSIONS & DRILLING PATTERNS FOR 1000 SERIES CASTORS





R6319

S1019