

STAINLESS STEEL EXCEL PLATE SERIES

UP TO 400KG / CASTOR



S4144B














S4114



S5142B

SUITABLE FOR WET ENVIRONMENTS
FULL STAINLESS CONSTRUCTION

SPECIFICATIONS & FITTINGS

 Diameter (mm)	 Width (mm)	 Wheel Type	 Wheel Code	 Bearing Type	 Load Capacity	 Height (mm)	 Swivel Radius	 With Brake	 Rigid Code	 Swivel Code
100	35	Reb Poly	RP4072	SS Roller	140/100	133	92	115	R4145	S4144
100	35	Nylon	NY401	Plain	200/150	133	92	115	R4143	S4142
100	36	Aluminium	AL473	Plain	180/150	133	92	-	R4115	S4114 *
100	36	Aluminium	AL474	Plain	180/150	133	92	-	R4141	S4140
100	35	GF Nylon	GF412	Plain	200/150	133	92	115	R4139	S4138
125	35	Reb Poly	RP5072	SS Roller	180/150	158	158	120	R5145	S5144
125	35	Nylon	NY501	Plain	200/150	158	158	120	R5143	S5142
150	50	Reb Poly	RP6074	SS Roller	300/250	187	127	160	R6137	S6136
150	40	Reb Poly	RP6072	SS Roller	300/250	187	127	160	R6145	S6144
150	50	Nylon	NY652	Plain	300/250	187	127	160	R6143	S6142
150	50	Nylon	NY655	SS Roller	300/250	187	127	160	R6141	S6140
200	50	Reb Poly	RP8072	SS Roller	300/250	237	156	170	R8145	S8144
200	45	Nylon	NY800	Plain	380/350	237	156	170	R8143	S8142
200	50	Nylon	NY802	SS Roller	380/350	237	156	170	R8141	S8140
200	43	GF Nylon	GF800	Plain	400/300	237	156	170	R8149	S8148

To order castor with Swivel Lock & Brake (B), add B to the end of the Swivel Code e.g. S5144B indicates a brake castor. *S4114 not available with brake.
Indicates castor suitable for high/low temperature applications.

Part numbers denoted in red indicate M2 Baseplate. Part numbers denoted in black indicate M3 Baseplate.

BASEPLATE DIMENSIONS & DRILLING PATTERNS FOR RIGID STAINLESS STEEL EXCEL CASTORS

BASEPLATE DIMENSIONS & DRILLING PATTERNS FOR SWIVEL STAINLESS STEEL EXCEL CASTORS

