

NEW

Rebound Rubber Wheels

RR4078

NEW

NEW PARTS ADDED

Rebound Rubber Tyred Wheels are non-marking, quiet and shock absorbing with a low rolling resistance. They are perfect for moving lightly loaded equipment over uneven ground, and protect the load from shocks.

They roll over small obstructions easily, and are ideal for waste bins, laundry trolleys, electrical equipment and other “handle with care” goods.

Stainless bearing models are available.

RR5078



Diameter (mm)	Tyre Width (mm)	Boss Width (mm)	Axle Diameter	Bearing Type	Load Capacity (kg)	Wheel Code
75	30	40	8mm or 3/8"	Ball	100/80	RR3348
75	32	40	8mm or 3/8"	SS Ball	100/80	RR3367
100	30	40	8mm or 3/8"	Ball	100/80	RR4473
100	32	40	8mm or 3/8"	SS Ball	100/80	RR4367
100	35	48	8mm, 3/8" or 12mm	Ball	150/110	RR4077
100	50	65	1/2" or 20mm	Ball	250/100	RR4078 NEW
125	30	40	8mm or 3/8"	Ball	100/80	RR5573
125	32	40	8mm or 3/8"	SS Ball	100/80	RR5637
125	35	48	8mm, 3/8" or 12mm	Ball	150/110	RR5077
125	50	65	1/2" or 20mm	Ball	250/100	RR5078 NEW
150	45	63	1/2" or 20mm	Ball	350/300	RR6677
200	45	63	1/2", 20mm or 3/4"	Ball	350/300	RR8871

Part numbers in blue indicate corrosion resistant wheels with 2 RS stainless steel bearings. These models are suitable for wash down applications and feature blue coloured threadguards to distinguish themselves from standard models.