

# Offset Puncture Proof WHEELS

Eliminates flat tyres, combining the strength and stability of a solid rubber wheel with the smooth cushioned ride of a pneumatic wheel, Richmond's puncture proof foam filled wheel is unrivaled in performance. The combination of this unique wheel compound with its offset hub fits this wheel to most hand trolleys requiring offset hubs.

3 piece zinc plated rim & rubber sealed precision bearings mean a longer life, ultimately reducing down time and increasing performance.



PF1047

Nom Wheel Diameter (mm)	Tyre Width (mm)	Boss Width (mm)	Axle Diameter	Bearing Type	Tyre Size	Tyre Tread Pattern	Load Capacity (kg)	Wheel Code
200	60	35 offset	3/4"	Flange	250x4	Industrial	100	PF8827
200	80	50 offset	3/4"	Ball	4.10x3.50x4	Industrial	100	PF1072
215	55	60 offset	5/8", 3/4" or 20mm	Ball	2.50 - 4	Lug	100	PF8881
255	85	54 offset	5/8", 3/4" or 20mm	Ball	4.10/3.50-4	Industrial	100	PF1047
280	60	60 offset	3/4"	Flange	2.50-6	Industrial	100	PF1124

# Offset Pneumatic WHEELS

Suitable for most hand trolleys requiring an offset wheel, Richmond's offset pneumatic wheel clearly stands alone as the best in the Australian market.

Fitted with the highest quality tough rubber tyre, 3 piece zinc plated rim and rubber sealed precision bearings to provide a longer life, ultimately reducing down time and increasing performance.



PN1070



REVERSE



Nom Wheel Diameter (mm)	Tyre Width (mm)	Boss Width (mm)	Axle Diameter	Bearing Type	Tyre Size	Tyre Tread Pattern	Load Capacity (kg)	Wheel Code
210	60	60 offset	3/4"	Ball	2.50-4	Lug	100	PN8872
260	85	54 offset	5/8", 3/4" or 20mm	Ball	4.10/3.50-4	Highway	180	PN1070
260	85	54 offset	5/8"	Flange	4.10/3.50-4	Industrial	180	PN1071
280	60	60 offset	3/4"	Flange	2.50-6	Industrial	150	PN1100