

CUSHION RUBBER WHEELS

Cushion Rubber Wheels offer a soft ride while having the ability to withstand high impact. A steel centre offers additional strength and load bearing capacity, with quality elastic rubber compound tyres which offer a softer, shock absorbing ride.



CR1060



SPECIFICATIONS



Diameter (mm)	Tyre Width (mm)	Boss Width (mm)	Axle Diameter	Bearing Type	Load Capacity	Wheel Code
230	40	60	20mm or 25mm	Ball	220/180	CR9000
250	50	55	12mm, 20mm or 25mm	Ball	300/250	CR1060
280	50	53	20mm, 25mm or 1"	Ball	200/170	CR1110

SOLID PNEUMATIC WHEELS

The unique formulation of these solid pneumatic wheels provides a pneumatic tyre performance with a much higher load capacity, towable up to 24KPH and ideal for tarmac use.

They are puncture proof for long wear, and feature split pins with rugged bolt on hubs.

Spare tyres stocked and fitted.



SN1612



SPECIFICATIONS



Diameter (mm)	Tyre Width (mm)	Boss Width (mm)	Axle Diameter	Bearing Type	Load Capacity	Wheel Code
250	75	93	20mm	Ball	260/200	SN1005
300	83	93	20mm or 25mm	Ball	540/400	SN1295
400	110	94	20mm, 25mm or 1"	Ball	950/730	SN1612
400	123	PCD	N/A	Ball	1050/810	SN1619