

# Beach Wheels

Richmond's beach wheels offer an easy rolling solution for navigating soft and uneven terrain.

Made from a polyurethane balloon tyre on a plastic hub, these wheels are perfect for use on soft sand, mud, gravel, grass and rock. These wheels can also handle harder surfaces such as concrete footpaths and roads.

The sturdy balloon tyre displaces the weight on uneven surfaces and offers qualities that keep the load moving.



BEACH10-20



BEACH12-1



BEACH16-1

Diameter	Wheel Width	Boss Width	Wheel Material	Bearing Type	Axle Diameter	Load Capacity	Wheel Code
250mm	120mm	74mm	Polyurethane	Plain bore	20	55kg	BEACH10-20
300mm	185mm	175mm	Polyurethane	Plain bore	1"	55kg	BEACH12-1
400mm	215mm	174mm	Polyurethane	Plain bore	1"	80kg	BEACH16-1


### 3 Sizes Available

**Easily Roll Over Soft & Uneven Surfaces!**

**Please note:** Beach wheels are designed to be inflated to a rating of 2-4 PSI only. They are meant to be slightly squishy like a balloon.

A bicycle pump is best for inflation. Compressed air can be used but care must be taken to ensure the wheels are not over-inflated.

**Axles & Axle Mounting Kits to Suit Available**



Available in 1" and 20mm Diameters

# Folding Beach Trolley

Featuring our new polyurethane beach wheels this lightweight trolley takes the hard work out of transporting items across sand and uneven surfaces.

The trolley frame folds flat with removable wheels for compact storage in spaces such as car boots.



Folded Dimensions	Dimensions	Wheel Size	Toe Plate	Load Capacity	Product Code
700(L) x 770(W) x 870(H)mm	700(L) x 770(W) x 1330(H)mm	300mm (12")	400mm(L) x 390mm (W)	40kg	FBHT0001

Removable  
Wheels

Padded  
Frame

Suitable For Loads  
Up To 40kg

# Puncture Proof Nylon Beach Wheels

Richmond's puncture proof nylon beach wheels offer a sturdy, easy rolling solution for navigating rougher and uneven terrain. Available in 3 sizes, these wheels are ready to handle whatever the terrain throws at them.

Low maintenance puncture proof tyres are airless, meaning you don't have to worry about flat tyres while moving your items across rough surfaces.



Diameter (mm)	Wheel Width (mm)	Boss Width	Wheel Material	Bearing Type	Axle Diameter	Load Capacity	Wheel Code
300mm	104mm	79mm	Nylon	Plain	1"	40	PF1104
300mm	147mm	117mm	Nylon	Plain	1"	50	PF1105
400mm	95mm	77mm	Nylon	Plain	1"	50	PF1695

**Axles & Axle Mounting Kits to Suit Available!**

# Plastic Centred Pneumatic Wheels

Richmond's plastic centred pneumatic wheels feature a quality corrosion and rust resistant plastic rim, making them ideal for applications in wet or damp environments.



Diameter	Tyre Width	Boss Width	Axle Diameter	Bearing Type	Tyre Size	Load Capacity	Wheel Code
215mm	60mm	62mm	3/4"	Nylon Bush	2.50-4	100	PN8864
265mm	88mm	60mm	3/4" or 20mm	Nylon Bush	4.10/3.50-4	100	PN1074
400mm	100mm	105mm	1"	Nylon Bush	4.00-8	200	PN1603
420mm	150mm	106mm	1"	Plain Bearing	16x6.50-8	200	PN1604

## Nylon Reducer Bushes

Designed to reduce bore sizes



Part Number	Size
NRR004	Reduces 1" to 5/8"
NRR005	Reduces 1" to 3/4"
NRR006	Reduces 1" to 20mm