

300 SERIES BOLT CASTORS

This castor series has a higher load capacity of up to 300kg, making it perfect for a wide range of uses.

In this range, nylon wheels are the most common choice for industrial and trolley applications, rebound rubber wheels are ideal for road cases and transportable crates, while poly nylon wheels are best suited for undercover and showroom displays.

- Large variety of wheel types
- Baseplate frame or single bolt hole frame



S5218B



 Diameter (mm)	 Width (mm)	 Wheel Type	 Wheel Code	 Bearing Type	 Load Capacity (kg)	 Height (mm)	 Swivel Radius	 With Brake	 Bolt Hole Size	 Swivel Code
100	35	Reb Rubber	RR4077	Ball	150	130	90	125	12	S4214
100	35	Reb Poly	RP4072	SS Roller	150	130	90	125	12	S4216
100	35	Poly Nylon	PU4408	Roller	200	130	90	125	12	S4218
100	38	Poly Ci	PU449	Ball	200	130	90	125	12	S4220
100	35	Nylon	NY401	Plain	200	130	90	125	12	S4222
100	35	Nylon	NY413	Ball	200	130	90	125	12	S4224
100	35	Glass Nylon	GF412	Plain	200	130	90	125	12	S4228*
100	36	Aluminium	AL474	Bronze Bush	200	130	90	-	12	S4230 *
100	36	Aluminium	AL472	Oilless Du bush	200	130	90	-	12	S4232 *
100	38	Cast Iron	Ci421	Plain	200	130	90	125	12	S4234 *
100	38	Cast Iron	Ci400	Ball	200	130	90	125	12	S4236 *
125	35	Reb Rubber	RR5077	Ball	200	157	112	125	12	S5214
125	35	Reb Poly	RP5072	SS Roller	200	157	112	125	12	S5216
125	35	Poly Nylon	PU5508	Roller	200	157	112	125	12	S5218
125	35	Poly Ci	PU549	Ball	200	157	112	125	12	S5220
125	35	Nylon	NY501	Plain	200	157	112	125	12	S5222
125	35	Nylon	NY513	Ball	200	157	112	125	12	S5224
150	50	Nylon	NY652	Plain	300	181	125	150	12	S6222
150	50	Nylon	NY613	Ball	300	181	125	150	12	S6224
150	45	Reb Rubber	RR6677	Ball	225	181	125	150	12	S6228
150	50	Reb Poly	RP6072	SS Roller	300	181	125	150	12	S6216



S4216



S5214



S5222

Brake Options

B = Brake


To order castors with Brake add B to end of swivel code e.g. S4214B

* indicates castors not available with brake

 indicates castors suitable for high/low temperature applications.

These castors have a 12mm bolt hole but can be reduced to suit an 10mm bolt with a reduction bush (top hat).

Reduction bushes available to suit 10mm fittings, code: 100RED12100BT



Castor Fitting Requirements

To fit this castor to a 20mm thick base requires a 50mm x 12mm set screw.