

BALLOON BEACH WHEELS

Balloon beach wheels are made from polyurethane and are ideal for use over soft sand, mud, gravel, grass and rock. They can also handle harder surfaces such as concrete footpaths and roads. They are commonly seen on wheelchairs and other mobility equipment.

- For use on soft and uneven terrain
- Commonly seen on wheelchairs and beach carts
- Plastic rust-free hub



UP TO
80KG
CAPACITY

BEACH16-1

Diameter (mm)	Wheel Width (mm)	Boss Width (mm)	Wheel Material	Bearing Type	Axle Diameter	Load Capacity (kg)	Wheel Code
250	120	74	Polyurethane	Plain bore	20mm	55	BEACH10-20
300	185	175	Polyurethane	Plain bore	1"	55	BEACH12-1
400	215	174	Polyurethane	Plain bore	1"	80	BEACH16-1



Easily Roll Over Soft or Uneven Surfaces!

Please note: Beach wheels are designed to be inflated to a rating of 2-4 PSI only. They are meant to be slightly squishy like a balloon. A bicycle pump is best for inflation. Compressed air can be used but care must be taken to ensure the wheels are not over-inflated.

PUNCTURE PROOF NYLON BEACH WHEELS

These wheels are ideal for use over rough and uneven terrain, and due to their solid nylon construction, will not puncture. They are commonly seen on kayak trolleys and other marine equipment.

- For use on rough and uneven terrain
- Commonly seen on kayak trolleys and marine equipment
- Solid nylon construction

Diameter (mm)	Wheel Width (mm)	Boss Width (mm)	Wheel Material	Bearing Type	Axle Diameter	Load Capacity (kg)	Wheel Code
300	104	79	Nylon	Plain	1"	40	PF1104
300	147	117	Nylon	Plain	1"	50	PF1105
400	95	77	Nylon	Plain	1"	50	PF1695



PF1105-1

Axles & Axle Mounting Kits to Suit Available



Available in 1" and 20mm Diameters