

# CUSHION RUBBER WHEELS

These wheels can withstand high impact while still offering a soft ride. The steel centre adds additional strength while quality elastic rubber compound tyres result in a softer, shock absorbing ride.

- Soft, shock absorbing ride
- Can withstand high impact



CR1060

 Wheel Diameter (mm)	 Tyre Width (mm)	 Boss Width (mm)	 Axle Diameter	 Bearing Type	 Load Capacity (kg)	 Wheel Code
230	40	50	12mm, 1/2", 3/4", 20mm, 25mm	Ball	220	CR9000
250	50	55	12mm, 1/2", 3/4", 20mm, 25mm	Ball	300	CR1060
280	50	53	20mm, 25mm or 1"	Ball	200	CR1110

# SOLID PNEUMATIC WHEELS

These wheels are puncture proof for long wear, and feature split pins with rugged bolt-on hubs. The unique formulation of these solid pneumatic wheels provides the performance of a pneumatic tyre but with a much higher load capacity. They are towable up to 24kph and are ideal for tarmac use.

- Towable up to 24kph
- Puncture proof
- High load capacity



SN1612

 Wheel Diameter (mm)	 Tyre Width (mm)	 Boss Width (mm)	 Axle Diameter	 Bearing Type	 Load Capacity (kg)	 Wheel Code
250	75	93	20mm, 25mm	Ball	260	SN1005
300	83	93	20mm, 25mm, 1"	Ball	540	SN1295
400	110	94	20mm, 25mm, 1"	Ball	950	SN1612
400	123	PCD	N/A	Ball	1050	SN1619

\*SN1005 and SN1295 solid pneumatic wheels are only towable for speeds up to 12kph