

# DONUT PROFILE POLY TYRED ALUMINIUM CENTRED WHEELS

UP TO  
**250KG**  
CAPACITY



PU815

These polyurethane tyred aluminium centred wheels require **20% less force to move than comparative wheels**. The reactive polyurethane wheel tread is chemically and mechanically moulded on to a lightweight aluminium centre.

- 20% less force to move
- Lightweight aluminium centre

 Wheel Diameter (mm)	 Tyre Width (mm)	 Boss Width (mm)	 Axle Diameter	 Bearing Type	 Load Capacity (kg)	 Wheel Code
75	30	32	12mm	Ball	150	<b>PU349</b>
100	50	66	1/2" or 20mm	Ball	150	<b>PU436</b>
125	50	66	1/2" or 20mm	Ball	200	<b>PU536</b>
150	50	66	1/2" or 20mm	Ball	200	<b>PU636</b>
200	50	66	1/2" or 20mm	Ball	250	<b>PU815</b>



PU349

## HEAVY INDUSTRIAL CASTORS WITH DONUT PROFILE WHEELS

Castors with **Swivel Lock & Brake** or **Directional Lock** also available



S4372

R4373

S5372

R5373

S6626

R6627

S8824

R8825

## 500 SERIES CASTORS WITH DONUT PROFILE WHEELS

Castors with **Swivel Lock & Brake** or **Directional Lock** also available



S6016

R6017

S8020

R8021