

POLY TYRED NYLON CENTRED WHEELS

UP TO
600KG
CAPACITY








These wheels are manufactured from injection moulded polyurethane around a nylon hub. They are hard wearing, non-marking and long lasting with high load carrying abilities.

These wheels are suitable for intermittent use only. If your application required continuous running usage, our engineering department can recommend more suitable polyurethane tyres.

- Hard wearing and non-marking
- High load capacities
- For intermittent use only



PU6071

 Wheel Diameter (mm)	 Tyre Width (mm)	 Boss Width (mm)	 Axle Diameter	 Bearing Type	 Load Capacity (kg)	 Wheel Code
75	30	41	8mm	SS Ball	80	PU3345
75	30	41	8mm or 10mm	Ball	80	PU3344
100	30	41	8mm	SS Ball	100	PU4439
100	30	41	8mm or 3/8"	Ball	100	PU4444
100	35	49	3/8" 1/2" or 3/4"	Roller	250	PU4408
100	50	63	1/2", 3/4" or 20mm	Ball	250	PU4409
125	27	41	8mm	SS Ball	100	PU5539
125	27	41	8mm or 3/8"	Ball	100	PU5555
125	35	49	3/4", 3/8" or 1/2"	Roller	250	PU5508
125	50	63	1/2", 3/4" or 20mm	Ball	350	PU5509
150	30	41	8mm	Ball	100	PU6660
150	50	63	1/2", 5/8, 3/4" or 20mm	Ball	400	PU6071
200	50	63	1/2", 5/8, 3/4" or 20mm	Ball	400	PU8071
200	50	48	20mm, 25mm or 1"	Ball	600	PU8074
200	50	63	3/4"	Roller	700	PU8079



PU4408



PU5555



PU8071