

**STAINLESS ELITE** 

BOLT CASTORS

## SUITABLE FOR WET ENVIRONMENTS **FULL STAINLESS CONSTRUCTION**

These castors are manufactured from grade 304 stainless steel for health and hygiene applications, such as on medical or laboratory equipment. They are also seen fitted to food carts that are frequently moved through coolrooms and steamy

Stainless steel double ball race swivel head

Stainless steel thread guard on 100mm and 125mm models

Plastic thread guard on 75mm models

kitchens. This range can be hose cleaned.

<b>O</b>					KG	J		3		Ī
Diameter (mm)	Width (mm)	Wheel Type	Wheel Code	Bearing Type	Load Capacity	Height (mm)	Swivel _ Radius	With Brake	Bolt Hole Size	Swivel Code
75	30	Poly Nylon	PU3345	SS Ball	80	105	70	105	12	S3384#
75	30	Nylon	NY3321	Plain	80	105	70	105	12	S3390#
75	32	Rebound Rubber	RR3367	SS Ball	80	105	70	105	12	S3391#
75	32	Elastic Rubber	ER3368	SS Ball	80	105	70	105	12	S3361#
100	27	Poly Nylon	PU4439	SS Ball	100	133	90	106	12	S4478
100	30	Nylon	NY4417	Plain	100	133	90	106	12	S4490
100	32	Rebound Rubber	RR4367	SS Ball	100	133	90	106	12	S4491#
100	32	Elastic Rubber	ER4368	SS Ball	100	133	90	106	12	S4461#
125	27	Poly Nylon	PU5539	SS Ball	100	159	102	106	12	S5578
125	30	Nylon	NY5517	Plain	100	159	102	106	12	S5590
125	27	Poly Nylon	PU5555	Ball	100	159	-	106	12	S5571B
125	32	Rebound Rubber	RR5367	SS Ball	100	159	102	106	12	S5591#
125	32	Elastic Rubber	ER5368	SS Ball	100	159	102	106	12	S5561#

Р





S4478B S5578

Pintles listed below suit all Stainless Elite Bolt Castors

Pintle	Pintle Type	Pintle Code		
10	For 19mm ID Round Tube	IPN12-P1		
	For 22mm ID Round Tube	IPN12-P2		
<b>新</b>	For 28.5mm ID Round Tube	IPN12-P3		
111	For 19mm ID Square Tube	IPN12-P4		
W	For 22mm ID Square Tube	IPN12-P5		
<b>1</b> 13	For 28.5mm ID Square Tube	IPN12-P6		

SEE page 117 FOR SOLID AND THREADED PINTLE OPTIONS

## **Brake Options**

S4361B

D = Directional Lock

To order castors with Brake add B or D to end of swivel code e.g. S5578B

100kg


# indicates castors not available with directional lock.

## **Castor Fitting** Requirements

To fit this castor to a 20mm thick base requires a 50mm x 12mm set screw. Reduction bush 100RED1210OBT available to allow fitting with 10mm set screw.

These castors have a 12mm bolt hole but can be reduced to suit an 8mm or 10mm bolt with a reduction bush (top hat).

> 12mm hole can be reduced to 8mm or 10mm



Reduction bushes available to suit 8mm fittings, code: 100RED12080BT

to suit 10mm fittings, code:

