

STAINLESS ELITE PLATE CASTORS

SUITABLE FOR WET ENVIRONMENTS
FULL STAINLESS CONSTRUCTION

UP TO
100KG
CAPACITY



S4110B



S3104




S4488B

										
Diameter (mm)	Width (mm)	Wheel Type	Wheel Code	Bearing Type	Load Capacity (mm)	Height (mm)	Swivel Radius (mm)	With Brake (mm)	Rigid Code	Swivel Code
50	20	Poly Nylon	NA	SS Ball	30	69	50	77	R261	S260
50	20	Nylon	NA	Plain	30	69	50	77	R263	S262
75	30	Poly Nylon	PU3345	SS Ball	80	107	70	105	R3383	S3382#
75	30	Nylon	NY3321	Plain	80	107	70	105	R3389	S3388#
75	32	Rebound Rubber	RR3367	SS Ball	80	107	70	105	R3387	S3386#
75	32	Elastic Rubber	ER3368	SS Ball	80	107	70	105	R3315	S3315#
100	27	Poly Nylon	PU4439	SS Ball	100	135	90	106	R4477	S4476
100	30	Nylon	NY4417	Plain	100	135	90	106	R4489	S4488
100	32	Rebound Rubber	RR4367	SS Ball	100	135	90	106	R4429	S4428#
100	32	Elastic Rubber	ER4368	SS Ball	100	135	90	106	R4416	S4415#
100	36	Aluminium	AL472	Oilless Du bush	100	135	90	-	R4493	S4492#
125	27	Poly Nylon	PU5539	SS Ball	100	161	102	106	R5577	S5576
125	30	Nylon	NY5517	Plain	100	161	102	106	R5589	S5588
125	32	Rebound Rubber	RR5367	Ball Bearing	80	159	102	106	R5529	S5528
125	32	Elastic Rubber	ER5368	SS Ball	100	161	102	106	R5516	S5515#


Brake Options

B = Brake
D = Directional Lock


To order castors with Brake or Directional Lock add B or D to end of swivel code e.g. S4476B



Baseplate for Rigid Castors



Baseplate for Swivel Castors



indicates castors not available with directional lock.